

The SmoothLite LED linear lighting products provide an even distribution of high output light. Highly efficient midpower LEDs running at constant current make the linear SmoothLite an excellent solution for a variety of lighting needs.



PRODUCT DETAILS

Intended Use

The SmoothLite LED overhead lights are designed for new projects or retro-fit projects.

Construction & Materials

High quality aluminum rail incorporating heat sink technology. High impact resistant mounting clips.

Optical System

Several different wide and narrow light distribution options available.

Electrical System

Class 2 low voltage LED driver; Input voltage 120V-277V

Installation

Quick and easy installation using the provided mounting clips.

Recommended Uses

Warehouses
Garages
Production Areas
Retail

Listings

UL Listed
RoHS Compliant
DLC Qualified
LED Lighting Facts Approved

Warranty

SmoothLite products come with a 10 year warranty for parts manufactured and furnished by Innovative Lighting, LLC. Standard terms and conditions apply.



MADE IN THE USA



SPEC INFORMATION

Part Number	Number of LEDs	CRI (nominal)	CCT (nominal)	Efficacy	Average L70 Life (hrs)	Dimensions	Weight	Energy (Watts)	Lumens (typical)	DLC/ES #
785-5226-4*	420	88.4	5308 K	102 lm/W	120,000	68.25"L 2.25"W 1.75"D	3.55 lbs (2x)	99.4	11520	P00000WVZ
785-6226-4*	420	86.4	4051 K	102 lm/W	120,000	68.25"L 2.25"W 1.75"D	3.55 lbs (2x)	99.5	10180	P00000WY4
785-6224-4*	280	86.4	4049 K	103 lm/W	120,000	46.13"L 2.25"W 1.75"D	2.55 lbs (2x)	64.5	6770	P00000WY3

*785-X22Y4 kit consists of two 785-X22Y-1 light fixtures.

Part Number	Number of LEDs	CRI (nominal)	CCT (nominal)	Efficacy	Average L70 Life (hrs)	Dimensions	Weight	Energy (Watts)	Lumens (typical)	DLC/EC #
785-5226-1	210	83.8	5311 K	124.2 lm/W	120,000	68.25"L 2.25"W 1.75"D	3.55 lbs	49.7	6212	P00000WW0
785-5224-1	140	86.4	5000 K	101.1 lm/W	120,000	46.13"L 2.25"W 1.75"D	2.55 lbs	33.3	3370	-----
785-6226-1	210	86.4	4000 K	103 lm/W	120,000	68.25"L 2.25"W 1.75"D	3.55 lbs	49.8	5106	P00000WXS
785-6224-1	140	86.4	4000 K	104 lm/W	120,000	46.13"L 2.25"W 1.75"D	2.55 lbs	32.7	3320	-----

PART NUMBER INFORMATION



Notes:

- 785-5226-4 & 785-6226-4 are DLC Qualified as High-Bay Fixtures for a 120V or 240V input
- 785-5226-4 & 785-6226-4 require two 785-9991-1 LED drivers or a Listed 785-9991-4 power unit
- 785-6224-4 requires two 785-9990-1 LED drivers or a Listed 785-9990-4 power unit
- 785-5226-1 & 785-6226-1 are DLC Qualified as Low-Bay Fixtures for a 120V only
- 785-5226-1 & 785-6226-1 require one 785-9991-1 LED driver or a Listed 785-9991-4-1 power unit
- 785-5224-1 & 785-6224-1 require one 785-9990-1 LED driver or a Listed 785-9990-4-1 power unit

