

The SmoothLite LED linear lighting products provide an even distribution of high output light. Highly efficient midpower LEDs running at constant current make the linear SmoothLite an excellent solution for a variety of lighting needs.



## PRODUCT DETAILS

### Intended Use

The SmoothLite LED overhead lights are designed for new projects or retro-fit projects.

### Construction & Materials

High quality aluminum rail incorporating heat sink technology. High impact resistant mounting clips.

### Optical System

Several different wide and narrow light distribution options available.

### Electrical System

Class 2 low voltage LED driver; Input voltage 120V-277V

### Installation

Quick and easy installation using the provided mounting clips.

### Recommended Uses

Warehouses  
Garages  
Production Areas  
Retail

### Listings

UL Listed  
RoHS Compliant  
DLC Qualified  
LED Lighting Facts Approved

### Warranty

SmoothLite products come with a 10 year warranty for parts manufactured and furnished by Innovative Lighting, LLC. Standard terms and conditions apply.



MADE IN THE USA



## SPEC INFORMATION

Part Number	Number of LEDs	CRI (nominal)	CCT (nominal)	Efficacy	Average L70 Life (hrs)	Dimensions	Weight	Energy (Watts)	Lumens (typical)	DLC/ES #
785-5226-4*	420	88.4	5308 K	102 lm/W	120,000	68.25"L 2.25"W 1.75"D	3.55 lbs (2x)	99.4	11520	P00000WVZ
785-6226-4*	420	86.4	4051 K	102 lm/W	120,000	68.25"L 2.25"W 1.75"D	3.55 lbs (2x)	99.5	10180	P00000WY4
785-6224-4*	280	86.4	4049 K	103 lm/W	120,000	46.13"L 2.25"W 1.75"D	2.55 lbs (2x)	64.5	6770	P00000WY3

\*785-X22Y4 kit consists of two 785-X22Y-1 light fixtures.

Part Number	Number of LEDs	CRI (nominal)	CCT (nominal)	Efficacy	Average L70 Life (hrs)	Dimensions	Weight	Energy (Watts)	Lumens (typical)	DLC/EC #
785-5226-1	210	83.8	5311 K	124.2 lm/W	120,000	68.25"L 2.25"W 1.75"D	3.55 lbs	49.7	6212	P00000WW0
785-5224-1	140	86.4	5000 K	101.1 lm/W	120,000	46.13"L 2.25"W 1.75"D	2.55 lbs	33.3	3370	-----
785-6226-1	210	86.4	4000 K	103 lm/W	120,000	68.25"L 2.25"W 1.75"D	3.55 lbs	49.8	5106	P00000WXS
785-6224-1	140	86.4	4000 K	104 lm/W	120,000	46.13"L 2.25"W 1.75"D	2.55 lbs	32.7	3320	-----

## PART NUMBER INFORMATION



### Notes:

- 785-5226-4 & 785-6226-4 are DLC Qualified as High-Bay Fixtures for a 120V or 240V input
- 785-5226-4 & 785-6226-4 require two 785-9991-1 LED drivers or a Listed 785-9991-4 power unit
- 785-6224-4 requires two 785-9990-1 LED drivers or a Listed 785-9990-4 power unit
- 785-5226-1 & 785-6226-1 are DLC Qualified as Low-Bay Fixtures for a 120V only
- 785-5226-1 & 785-6226-1 require one 785-9991-1 LED driver or a Listed 785-9991-4-1 power unit
- 785-5224-1 & 785-6224-1 require one 785-9990-1 LED driver or a Listed 785-9990-4-1 power unit

